



## MIURA II PLUS

### AUTOMATIC XY CUTTER WITH VERTICAL ALIGNMENT

High performing cutting machine for X and Y trimming of flexible materials  
with automatic vertical cutting correction.

- > Combined horizontal and vertical cutting for the fastest finish for your printed and unprinted rolls
- > Maximum precision thanks to the **EDGE CONTROL** that reads the line longitudinally printed along the entire length of the roll
- > High performing trimmer: cut one roll of 50 meters (164 ft) in 3 minutes
- > 3 operation modes: crop mark (useful to trim multiple printing sizes from the same roll), automatic and manual

**NEW**

Even more intuitive set up parameters thanks to the new designed user-friendly software (LCD touch screen display). New **MUTING** function that avoids possible misreading of hidden marks

- > Available in roll to sheet (Miura II Plus) and roll to rolls version (up to 3 rolls) (Miura II Plus WP - wallpaper)

#### SUITABLE FOR:

- Paper (also laminated or encapsulated)
- Wallpaper
- Vinyl & self adhesive vinyl
- Backlit & frontlit display
- Reflective material
- PVC banner (up to 900 gr/m<sup>2</sup> - 27 oz./ya<sup>2</sup>)
- Magnetic rubber
- Polycarbonate (film)
- Canvas & polyester (with liner)
- Many more..






Automatic vertical alignment control panel



Optical sensor for vertical alignment



Advanced cutting mark reader



New software design for better usability



Fine positioning of the cutting blades (optional)



Fine pressure adjustment (according to the types of material)



Adjustable collecting table (optional)



Single lengthwise rotary crush cutter (twin cutters optional)



Miura II Plus WP for wallpaper: equipped with front rewinding shafts with independent clutches and speed regulator

	MIURA II 160 PLUS MIURA II 265 PLUS	MIURA II 160 PLUS WP (WALLPAPER)
Working width	1650 mm (65 in) 2650 mm (105 in)	1650 mm (65 in)
Maximum cutting thickness	1,2 mm (0,04 in)	1,2 mm (0,04 in)
Feeding speed	1 - 30 m/min. (3 - 98 ft/min)	1 - 15 m/min (3 - 49 ft/min)
Usable cutting units	max. 8	max. 8
Cross cutting speed	5 - 120 m/min (16 - 393 ft/min)	5 - 120 m/min (16 - 393 ft/min)
Max. roll diameter	300 mm (12 in)	300 mm (12 in)
Max. roll weight	60 kg (132 lb)	60 kg (132 lb)
Power supply	230 V - 50 Hz - 650 W	230 V - 50 Hz - 650 W
Dimensions (W x D x H)	2400 x 1200 x 1350 mm (94 x 47 x 53 in) 3500 x 1200 x 1350 mm (137 x 47 x 53 in)	2500 x 1200 x 1300 mm (99 x 48 x 51 in)
Weight	340 kg (749 lb) / 510 kg (1124 lb)	410 kg (903 lb)
Packing dimensions (W x D x H)	2650 x 1300 x 1400 mm (104 x 51 x 55 in) 2750 x 1300 x 1400 mm (108 x 51 x 55 in)	2650 x 1300 x 1400 mm (104 x 51 x 55 in)
Packing weight	425 kg (936 lb) / 595 kg (1312 lb)	480 kg (1058 lb)

Manufactured in compliance with CE regulations



100% Made by FLEXA  
100% Made in Italy

Pratite nas:    

Distributor

 **Sitotehnika**

Jugoslovenska 2, 11250 Beograd  
Tel: +381 11 6581274, 6581275  
www.sitotehnika.net  
office@sitotehnika.net

 **ST Graf**

Aerodromska 17, 71000 Sarajevo, tel: +387 33 719095, 66 002600, e-mail: sasastgraf@gmail.com  
Pilanska bb, 78000 Banja Luka, tel: +387 51 305280, 66 002400, e-mail: stgrafbl@gmail.com  
Lagja Kalabria pn, 10000 Priština, tel: +383 38 602080, 45 600641, e-mail: info@stgraf-ks.com  
Bulevar Boris Trajkovski 112, 1000 Skoplje, tel: +389 78 290996, e-mail: ace@sitotehnika.net