

Product Information

Mod.R&S 05 | Rev.4 | Update 08/2019 | Page 1



VIDEOFLEX ®

Description Plotter cut heat seal material with non adhesive polyester backing. One of the most requested Siser cut materials, due to its resistant softness and feel. Specifically conceived for the sports industry.

> Suitable for cotton, polyester, blends of these materials, not treated or dye sublimated fabrics.

- Usage Mirror cut the material
 - · Weed the exceeding material
 - · Place the material on the garment with its polyester backing
 - · Heat apply at the conditions shown on the right
 - · Remove the carrier cold

Washing Wait at least 24 hours from application before washing. Washing resistance up to 80°C, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, cotton cycle.

> The product is REACH compliant The product is Öko-Tex® Standard 100 Class I certified The product is VEGANOK certified







Average thickness 250 microns

Suggested cutting settings

Blade: 60° Pressure: 40 gf Speed: 20 cm/sec

Transfer settings 15 seconds at 150°C (302°F)

medium pressure (3-4 bar)

Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



Management ISO 9001:2015 ISO 14001:2015



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com.

For further information, please contact our Sales Office.













