

## **Product Information**

Mod.R&S06 | Rev.4 | Update 05/2020 | Page 1



## **BRICK 600**


Description Thick PU plotter cut material, with polyester backing, available with matt finish.

> Despite the outstanding thickness, the material grants easy cutting, weeding and application and a high washing resistance. Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex, not treated or dve sublimated.

## Usage Preheat the press for 2 minutes at 155°C.

- · Mirror cut the material
- · Weed the exceeding material
- · Place the material on the garment with its polyester backing
- · Heat apply at the conditions shown on the right
- · Remove the carrier cold





Blade: 60° Pressure: 80 gf Speed: 10 cm/sec



25 seconds at 155°C (310°F) high pressure (4-5 bar)

Washing Wait at least 24 hours from application before washing. Washing resistance up to 60°C, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, cotton program.

> The product is REACH compliant The product is Öko-Tex® Standard 100 Class II certified The product is VEGANOK certified







Washing temperature 60

Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience.

> We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C.



Management System ISO 9001:2015 ISO 14001:2015





The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com. For further information, please contact our Sales Office.











