

JFX600-2531



High performance, extreme efficiency

The JFX600-2531 wide format flatbed printer boasts high speed production with full board printing in under 60 seconds. With its quick registration system, semi-automated maintenance, and extra-large print area of 8'x10', it fits as perfectly in a high-volume packaging or POP shop as it does in specialized architectural and interior design. With its advanced toggle functionality, it can increase efficiency in any shop.

- Extra-large 8' x 10' print area
- Print speeds up to 2,152 ft2/hr
- Updated Toggle Print for high efficiency
- 9 Vacuum zones
- Easy navigation touch screen MPC
- Industry leading Core Technologies
- loT ready
- PICT remote monitoring
- Uses Greenguard Gold certified inks

For best results, always use Mimaki original inks.



Printhead	Sixteen staggered on-demand piezo heads
Print Resolutions	600, 1200 dpi
Print Speed (4 Color Mode)	2152 ft2/hr (200 m2/hr)
Maximum Print Area	98.43" x 122.05" (2500 mm x 3100 mm)
Maximum Media Size	100.43" x 124.05" (2550 mm x 3150 mm)
Vacuum Zones	9 zones (4 zones front and back with a center zone)
Maximum Media Thickness	up to 2.36" (60 mm)
Maximum Media Weight	10 lb/ft2 (50 kg/m2)
Ink Type	600, 1200 dpi 2152 ft2/hr (200 m2/hr) 98.43" x 122.05" (2500 mm x 3100 mm) 100.43" x 124.05" (2550 mm x 3150 mm) 9 zones (4 zones front and back with a center zone) up to 2.36" (60 mm) 10 lb/ft2 (50 kg/m2) Rigid: LH-100 ink; C, M, Y, K, Lc, Lm, W, Clear. Flexible: LUS-150 ink; C, M, Y, K, Lc, Lm, W with LUS-100 Clear LUS-120 ink; C, M, Y, K, Lc, Lm, W, Clear.
Ink Package Size	1 L bottle
Interface	Ethernet 10,000 BASE-T
Power Supply	1 L bottle Ethernet 10,000 BASE-T single phase AC200-240±10% 50/60 Hz±1 Hz 24Ax3
Power Consumption	Less than 4.8kWhr x3
Operational Environment	Temperature 68° – 86° F (15-30° C) Humidity: 35–65 % RH (Non condensing) 213" W x 191" D x 67" H (5400mm W x 48500mm D x 1700mm H)
Dimensions (W \times D \times H)	213" W x 191" D x 67" H (5400mm W x 48500mm D x 1700mm H)
Weight	3527 lbs (1600 kg)
Options	Primer installation kit lonizer Unit 3 Higher power vacuum units (3phase-200, single phase-200, 3phase-400 with blower connection kit 3 L Bulk Ink System loT MDL Module
Certifications	UL62368, CE Marking (EMC Directive, Machinery Directive), RoHS / REACH / EAC / RCM Mark, KC Certification, UKCAmark







Aerodromska 17, 71000 Sarajevo, tel: +387 66 002600, e-mail: aleksandar@sitotehnika.net Pilanska bb, 78000 Banja Luka, tel: +387 51 305280, 66 002400, e-mail: stgrafbl@gmail.com Lagja Kalabria pn, 10000 Priština, tel: +383 38 602080, 45 600641, e-mail: info@stgraf-ks.com Bulevar Boris Trajkovski 112, 1000 Skoplje, tel: +389 78 290996, e-mail: ace@sitotehnika.net