



Mimaki DTF štampač

TxF150-75
TxF300-75

- ✓ Stabilan rad & vrhunski kvalitet
- ✓ Mimaki DTF pigmentna boja CMYK + W
- ✓ OEKO-TEX sertifikat
- ✓ Funkcija provere i zamene mlaznica
- ✓ Cirkulacija bele boje protiv zgrušavanja



DTF šejker

LIGHT60

Šeker za nanošenje lepka i sušenje ✓

Velika površina aplikacije do 600 mm ✓

Podesivi dovod medija ✓



PET film
rolna 60cm/80cm





Kanvas Torbe/Patike



DTF Preslikač



Futrole



Majice



Dukserice



Pantalone



Etikete



Jakne

DTF štampač TxF150-75 / TxF300-75

SPECIFIKACIJA

Brzina štampe u najboljem kvalitetu	2.6m/h (720x720 10 prolaza Bi Hi) / 7.5m/h (720x720 6 prolaza Bi Hi)
Maks. širina štampe	800mm
Maks. širina materijala	810mm
Debljina materijala	1.0mm ili manje
Težina rolne	45kg
Boja	PHT50 pigmentna boja CMYK + W (OEKO-TEX sertifikat)
Pakovanje boje	Aluminijumsko pakovanje od 600ml (CMYK) i 500ml (W)
Povezivanje	USB2.0 Hi-speed, Ethernet 1000BASE-T
Napajanje	Jedna faza AC100~120V/200~240V±10%, 50/60Hz±1Hz x1
Radno okruženje	Temperatura: 20~30°C, Vlažnost: 35~64% RH (bez kondenzacije)
Dimenzije mašine	1,965mm x 700mm x 1,392mm
Težina mašine	126kg
Sekač materijala	Instaliran
RIP Softver	RasterLink7 (uključen)

DTF šejker LIGHT60

SPECIFIKACIJA

Maksimalna širina rolne	600mm
Raspon radne temperature	0-160°C
Napajanje	110v/220v
Snaga	4kW
Dimenzije mašine	1,010mm x 1,030mm x 970mm
Težina mašine	140kg


DTF air filter - dodatak za šejker Light60

SPECIFIKACIJA

Broj elemenata filtera	3 nivoa (junior, intermedium, advanced)
Protok	310m³/h
Efikasnost filtera	0,3um 99.97%
Napajanje	110v/220v
Snaga	210W
Dimenzije mašine / dužina creva	430mm x 250mm x 457mm / 1,4m
Težina mašine	16kg



junior filter



intermedium filter



advanced filter



air filter